



Sometimes great colour
requires lots of effort.

Sometimes it doesn't.

Lexmark C532n

Outstanding value in colour
laser printing for small
workgroups!

Captivating colour

Make a great impression on your documents, thanks to Lexmark's advanced colour technology and the enhanced detail of vivid 4800 Colour Quality printing.

Rapid results

With lightening-fast colour speeds of up to 21 ppm, and just 10.5 seconds to first print in mono, your presentations and reports are practically ready before you are.

Effortless operation

Simplify your workflow with an intuitive new operator panel, 100% front-access consumables, and an optional second input drawer for less reloading.

Up to 22 ppm mono,
21 ppm colour

4800 Colour Quality

Optional 550-sheet drawer

LEXMARKTM

Lexmark C532n/dn

Full-speed ahead of your expectations

Offering you an exceptional price-performance ratio, Lexmark's network-ready C532n colour laser is the perfect device for the everyday needs of your hardworking office. It delivers lively, brilliant colour at rapid-fire speeds, enhancing your documents and productivity at the same time. And, best of all, it makes working a whole lot easier for everyone!

Happy, hassle-free printing

With the intuitive operator panel, printing and maintenance are as easy as child's play. It combines a large, all-points-addressable 4-line display, intuitive navigation buttons, and easy-access menu selections. Plus, for even more simplified troubleshooting, you benefit from built-in help guides, as well as helpful 'Show Me' messaging for extra clarity.

A greener approach

Why not save energy, paper and money at the same time? The Lexmark C532n reduces costs to you and the planet. It includes a new Eco Mode, which enables you to minimise power consumption and paper waste. What's more, you can opt for a duplex printing model (Lexmark C532dn) to cut paper waste in half.

Print Technology

Colour Laser

Print Speed (A4 mono)

Up to 22 ppm

Print Speed (Letter, Colour)

Up to 22 ppm

Print Speed (A4 colour)

Up to 21 ppm

Print Speed (Letter mono)

Up to 24 ppm

Time to First Page (Black)

as fast as 10.5 seconds

Time to First Page (Colour)

as fast as < 11 seconds

Print Resolution, Black

1200 x 1200 dpi

4800 Color Quality (2400 x 600 dpi)

Print Resolution, Colour

1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)

Processor

375 MHz

Memory, standard

128 MB

Memory network model, maximum

640 MB

Expandable Memory Options

Yes

Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0

Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, SUSE Linux Enterprise Server 8.0, 9.0, SUSE Linux Professional 9.1, 9.2, 9.3, Debian GNU/Linux 3.0, 3.1, Linspire Linux 4.5, 5.0, SUSE Linux 10.0, 10.1

Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), Me, XP, Server 2003, 98 2nd Edition, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Vista

Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.11, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

Paper Handling (Standard)

250-Sheet Output Bin, Single Sheet Manual Feed Slot, 250-Sheet Input Tray

Paper Handling Optional

550-Sheet Drawer

Paper Input Capacity (Standard)

250 pages at 80 gsm bond

Paper Input Capacity (Maximum)

800 pages at 80 gsm bond

Paper Output Capacity (Standard)

250 pages at 80 gsm bond

Paper Output Capacity (Maximum)

250 pages at 80 gsm bond

Envelope Capacity

1

Finishing Option

No

Number of Paper Inputs

2

Number of Paper Inputs, Maximum

3

Media Types Supported

Card Stock, Envelopes, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal

Standard Ports

Ethernet 10/100BaseTX (RJ-45), USB Compatible with USB 2.0 Specification

Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7000e Fast Ethernet (USB)

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, Enhanced IP (Port 9400), FTP, TFTP

Network Protocol Support

TCP/IP IPv4, AppleTalk™, TCP/IP IPv6

Printable Area

4.2 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation (and PostScript 3 Emulation on E250dn), Personal Printer Data Stream (PPDS), PostScript 3 Emulation, PDF 1.5, xHTML

Packaged Size (mm - H x W x D)

570 x 633 x 553 mm

Size (mm - H x W x D)

484 x 440 x 512 mm

Weight (kg)

25.9 kg

Noise Level, Idle

31 dBA

Noise Level, Operating

53 dBA

Product Guarantee

One Year Onsite Repair, Next Business Day response time

Product Certifications

Energy Star, CSA, ICES Class B, BSMI Class B, VCCI Class B, FCC Class B, UL 60950 3rd Edition, IEC 320-1, CE Class B, CB IEC 60950, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class B, CCC Class B, CISPIR 22 Class B, MIC Mark

Duty Cycle

Up to 75,000 one-time maximum Pages

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)

Cartridges

Ships with 4K* Black and 3K** Colour Return Programme Toner Cartridges

Aftermarket cartridges available :
5K** and 3K** CMY Return Programme Toner Cartridges.
4K* Black CMY Return Programme Toner Cartridges.

Regular Cartridges also available.

* Up to this number of Standard pages. Average continuous black declared cartridge yield in accordance with ISO/IEC 19798 (FDIS).

** Up to this number of Standard pages. Average continuous composite CMY declared cartridge yield in accordance with ISO/IEC 19798 (FDIS).

Cost saving & environmental features

Energy Star compliant - Print and hold (verify print), multi-up printing, quality printing on recycled paper and integrated duplex printing (C532dn model) help reduce paper consumption - Selectable toner-saving modes help reduce the amount of toner used on a page - Return Programme cartridges and end-of-life product management help reduce landfill.

Models available

C532n — Network
C532dn — Duplex, Network



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

www.lexmark.co.uk

LEXMARK
TM